

# RETRACTORS

<b>F</b>	0.4 - 10.0 kg
1.0 - 22.0 lb	<b>RETRACTORS</b>

- Easy tension adjustment with no special tools required
- Heavy-duty steel construction for long life
- Long-lasting mainspring designed to minimize spring flexing and fatigue
- Tool can be set at desired position with adjustable cable stop
- Durable  $\frac{3}{32}$ "-diameter stranded steel aircraft cable
- Ratchet lock (on FLR models) locks out retraction tension for unrestricted tool movement (ON/OFF switchable)

## *F Retractors*

model	weight range (kg)	travel (m)	weight range (lb)	travel (ft)
5F	0.4 – 2.3	2.4	1.0 – 5.0	8.0
10F	1.8 – 4.5	2.4	4.0 – 10.0	8.0
15F	3.6 – 6.8	2.4	8.0 – 15.0	8.0
22F	7.3 – 10.0	2.4	16.0 – 22.0	8.0

## *FLR Retractors* with Ratchet Locks

model	weight range (kg)	travel (m)	weight range (lb)	travel (ft)
5FLR	0.4 – 2.3	2.4	1.0 – 5.0	8.0
10FLR	1.8 – 4.5	2.4	4.0 – 10.0	8.0
15FLR	3.6 – 6.8	2.4	8.0 – 15.0	8.0
22FLR	7.3 – 10.0	2.4	16.0 – 22.0	8.0



See page 24 for dimensions